



Safety Data Sheet

Material Name: SAFETY-KLEEN PREMIUM SOLVENT (VIRGIN AND RECYCLED)

SDS ID: GHS 82658

*** Section 1 - Identification ***

Product Identifier

SAFETY-KLEEN PREMIUM SOLVENT (VIRGIN AND RECYCLED)

Product Code

None.

Synonyms

Safety-Kleen Premium Gold Solvent; Safety-Kleen Continued Use Product Solvent (CUP); High Flash Degreasing Solvent; Parts Washer Solvent; Petroleum Distillates; Petroleum Naphtha; Naphtha, Solvent; Mineral Spirits

Recommended Use

Cleaning and degreasing metal parts. If this product is used in combination with other products, refer to the Safety Data Sheets for those products.

Restrictions on Use

None known.

Manufacturer Information

Safety-Kleen Systems, Inc.
2600 North Central Expressway
Suite 400
Richardson, TX 75080
www.safety-kleen.com

Phone: 1-800-669-5740

Emergency # 1-800-468-1760

Issue Date

September 2, 2014

Supersedes Issue Date

November 8, 2012

Original Issue Date

January 26, 1995

*** Section 2 - Hazard(s) Identification ***

Classification in Accordance with 29 CFR 1910.1200.

Flammable Liquids, Category 4

Specific Target Organ Toxicity - Single Exposure, Category 3 (central nervous system)

Aspiration Hazard, Category 1

GHS LABEL ELEMENTS

Symbol(s)



Signal Word

DANGER!

Hazard Statement(s)

Combustible liquid

May cause drowsiness and dizziness

May be fatal if swallowed and enters airways

Safety Data Sheet

Material Name: SAFETY-KLEEN PREMIUM SOLVENT (VIRGIN AND RECYCLED)

SDS ID: GHS 82658

Precautionary Statement(s)

Prevention

Keep away from flames and hot surfaces. - No smoking. Wear protective gloves and eye/face protection. Avoid breathing vapor or mist. Use only outdoors or in a well-ventilated area.

Response

In case of fire: Use Class B/C or Class A/B/C fire extinguisher, carbon dioxide, regular foam, dry chemical, water spray, or water fog for extinction. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

Storage

Store in a well-ventilated place. Keep container tightly closed. Keep cool.

Disposal

Dispose of in accordance with all applicable federal, state and local regulations.

Hazard(s) Not Otherwise Classified

None known.

*** Section 3 - Composition / Information on Ingredients ***

CAS	Component	Percent
64742-47-8	Distillates (petroleum), hydrotreated light	100

*** Section 4 - First Aid Measures ***

Description of Necessary Measures

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin

IF ON SKIN: Wash with plenty of soap and water. Remove contaminated clothing and wash before reuse. Get medical attention if irritation develops or persists.

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops or persists.

Ingestion

IF SWALLOWED: Aspiration hazard. Do NOT induce vomiting. If vomiting occurs, keep head lower than hips to help prevent aspiration. Call a poison control center or doctor immediately for treatment advice.

Most Important Symptoms/Effects

Acute

Central nervous system depression

Delayed

Central nervous system damage

Indication of Immediate Medical Attention and Special Treatment Needed, If Needed

IF exposed: Call a POISON CENTER or doctor/physician. Treat symptomatically and supportively. Treatment may vary with condition of victim and specifics of incident. Call 1-800-468-1760 for additional information.

*** Section 5 - Fire-Fighting Measures ***

Suitable Extinguishing Media

Class B/C or Class A/B/C fire extinguisher, carbon dioxide, regular foam, regular dry chemical, water spray, water fog.

Safety Data Sheet

Material Name: SAFETY-KLEEN PREMIUM SOLVENT (VIRGIN AND RECYCLED)

SDS ID: GHS 82658

Unsuitable Extinguishing Media

Do not use high-pressure water streams.

Specific Hazards Arising from the Chemical

Combustible liquid and vapor. The vapor is heavier than air. Vapors or gases may ignite at distant ignition sources and flash back. Run-off to sewer may create a fire hazard. Heated containers may rupture or be thrown into the air. Empty containers may retain product residue including flammable/explosive vapors. Product may be sensitive to static discharge, which could result in fire or explosion.

Hazardous Combustion Products

Decomposition and combustion materials may be toxic - Burning may produce carbon monoxide and unidentified organic compounds.

Special Protective Equipment and Precautions for Firefighters

A positive-pressure, self-contained breathing apparatus (SCBA) and full-body protective equipment are required for fire emergencies.

Fire Fighting Measures

Keep away from sources of ignition - No smoking. Keep unnecessary people away, isolate hazard area and deny entry. Move container from fire area if it can be done without risk. Cool containers with water spray until well after the fire is out. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible withdraw from area and let fire burn. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. Stay away from the ends of tanks. For tank, rail car or tank truck, evacuation radius: 800 meters (1/2 mile). Stay upwind and keep out of low areas. Dike for later disposal.

NFPA Ratings: Health: 1 Fire: 2 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

* * * Section 6 - Accidental Release Measures * * *

Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment. See **Section 8 – Exposure Controls/Personal Protection**. Avoid release to the environment.

Methods and Materials for Containment and Clean Up

Remove all ignition sources. Do not touch or walk through spilled product. Stop leak if you can do it without risk. Wear protective equipment and provide engineering controls as specified in **Section 8 – Exposure Controls/Personal Protection**. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Ventilate area and avoid breathing vapor or mist. A vapor suppressing foam may be used to reduce vapors. Contain spill away from surface water and sewers. Contain spill as a liquid for possible recovery, or sorb with compatible sorbent material and shovel with a clean, sparkproof tool into a sealable container for disposal. Additionally, for large spills: Water spray may reduce vapor, but may not prevent ignition in closed spaces. Dike far ahead of liquid spill for collection and later disposal.

There may be specific regulatory reporting requirements associated with spills, leaks, or releases of this product. Also see **Section 15 – Regulatory Information**.

* * * Section 7 - Handling and Storage * * *

Precautions for Safe Handling

Keep away from heat, sparks, or flame. Where flammable mixtures may be present, equipment safe for such locations should be used. When transferring product, trucks and tank cars should be grounded and bonded. Do not breathe vapor or mist. Use in a well-ventilated area. Avoid contact with eyes, skin, clothing, and shoes. Do not smoke while using this product.

Conditions for Safe Storage, Including Any Incompatibilities

Keep containers away from heat, flame, sparks, static electricity, or other sources of ignition. Keep container tightly closed. Keep cool. Do not pressurize, cut, weld, braze, solder, drill, or grind containers. Empty product containers may retain product residue and can be dangerous. Store in a well-ventilated place. See **Section 14 – Transportation Information** for Packing Group information.

Safety Data Sheet

Material Name: SAFETY-KLEEN PREMIUM SOLVENT (VIRGIN AND RECYCLED)

SDS ID: GHS 82658

Incompatibilities

Strong oxidizing materials.

* * * Section 8 - Exposure Controls / Personal Protection * * *

Component Exposure Limits

Distillates (petroleum), hydrotreated light (64742-47-8)

ACGIH:	100 ppm TWA (related to Stoddard solvent)
OSHA Final:	500 ppm TWA; 2900 mg/m ³ TWA (related to Stoddard solvent)
OSHA Vacated:	100 ppm TWA; 525 mg/m ³ TWA (related to Stoddard solvent)
NIOSH:	350 mg/m ³ TWA (related to Stoddard solvent)
	1800 mg/m ³ Ceiling (15 min, related to Stoddard solvent)

Appropriate Engineering Controls

Provide general ventilation needed to maintain concentration of vapor or mist below applicable exposure limits. Where adequate general ventilation is unavailable, use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below applicable exposure limits. Where explosive mixtures may be present, equipment safe for such locations should be used.

Individual Protective Measures, such as Personal Protective Equipment

Personal protective equipment should be selected based upon the conditions under which this material is used. A hazard assessment of the work area for PPE requirements should be conducted by a qualified professional pursuant to regulatory requirements. The following PPE should be considered the minimum required: safety glasses, gloves, lab coat or apron.

Eyes/Face Protection

Safety glasses with side shields should be worn at a minimum. Additional protection such as goggles, face shields, or respirators may be needed depending upon anticipated use and concentrations of mists or vapors. Provide an emergency eye wash fountain and quick drench shower in the immediate work area. Contact lens use is not recommended.

Skin Protection

Where skin contact is likely, wear neoprene, nitrile, or equivalent protective gloves; use of natural rubber or equivalent gloves is not recommended. To avoid prolonged or repeated contact with products where spills and splashes are likely, wear appropriate chemical-resistant faceshield, boots, apron, coveralls, long sleeve shirts, or other protective clothing.

Respiratory Protection

Use NIOSH-certified P- or R- series particulate filter and organic vapor cartridges when concentration of vapor or mist exceeds applicable exposure limits. Protection provided by air purifying respirators is limited. Do not use N-rated respirators. Selection and use of respiratory protective equipment should be in accordance in the USA with OSHA General Industry Standard 29 CFR 1910.134; or in Canada with CSA Standard Z94.4.

Safety Data Sheet

Material Name: SAFETY-KLEEN PREMIUM SOLVENT (VIRGIN AND RECYCLED)

SDS ID: GHS 82658

*** Section 9 - Physical & Chemical Properties ***

Appearance/Odor : Liquid, clear, colorless to pale yellow
Mild hydrocarbon odor

pH: Not applicable

Odor Threshold: 30 ppm (based on Stoddard Solvent)

Boiling Point: 350°F (177°C) (initial)

Melting Point: -45°F (-43°C) (maximum)

Solubility (H₂O): Insoluble.

Specific Gravity: 0.77 to 0.82 at 60°F (15.6°C)
(water = 1)

Density: 6.4 to 6.7 LB/US gal (770 to 800 g/l)

Octanol/H₂O Coeff.: Not available

Evaporation Rate: <0.1 (butyl acetate = 1)

Auto Ignition 480°F (249°C) (minimum)

Temperature:

LFL: 0.7 VOL% (minimum)

Flash Point: 148°F (64°C) (minimum)

UFL: 5 VOL% (maximum)

Viscosity: Not available

Vapor Pressure: 0.2 mm Hg at 68°F (20°C);

Vapor Density: 5 (air = 1) (approximately)

0.6 mm Hg at 100°F (37°C)

0.012 psia @ 100°F

Other Property Information

No information is available.

*** Section 10 - Stability & Reactivity ***

Reactivity

No reactivity hazard is expected.

Chemical Stability

Stable under normal temperatures and pressures.

Possibility of Hazardous Reactions

Will not polymerize under normal temperature and pressure conditions.

Conditions To Avoid

Avoid heat, sparks, flames, and other sources of ignition Avoid contact with incompatible materials.

Incompatible Materials

Avoid acids, alkalies, oxidizing agents, reducing agents, or reactive halogens.

Hazardous Decomposition Products

None under normal temperatures and pressures. See also **Section 5: Hazardous Combustion Products.**

*** Section 11 - Toxicological Information ***

Toxicity Data and Information

Component Analysis - LD₅₀/LC₅₀

Distillates (petroleum), hydrotreated light (64742-47-8)

Inhalation LC₅₀ Rat >5.2 mg/L 4 h; Oral LD₅₀ Rat >5000 mg/kg; Dermal LD₅₀ Rabbit >2000 mg/kg

Information on Likely Routes of Exposure

Inhalation

May cause irritation, nausea, loss of appetite, headache, drowsiness, dizziness, disorientation, tremors, lung damage (from aspiration), convulsions, and coma.

Ingestion

May cause headache, drowsiness, dizziness, loss of coordination, and aspiration hazard.

Skin Contact

May cause irritation of the skin.

Eye Contact

No information on significant adverse effects.

Safety Data Sheet

Material Name: SAFETY-KLEEN PREMIUM SOLVENT (VIRGIN AND RECYCLED)

SDS ID: GHS 82658

Immediate Effects

Central nervous system depression, lung damage (from aspiration), respiratory tract irritation, skin irritation.

Delayed Effects

Central nervous system damage, respiratory system damage.

Irritation/Corrosivity

Respiratory tract irritation, skin irritation.

Respiratory Sensitization

No information available for the product.

Skin Sensitization

No information available for the product.

Carcinogenicity

No carcinogenicity data available for this product.

Component Carcinogenicity

None of this product's components are listed by ACGIH, IARC, OSHA, NIOSH, or NTP.

Germ Cell Mutagenicity

Based on best current information, there is no known mutagenicity associated with this product.

Teratogenicity

No information available for the product.

Reproductive Effects

No epidemiological data is available for this product.

Specific Target Organ Effects - Single Exposure

Central nervous system.

Specific Target Organ Effects - Repeated Exposure

Central nervous system.

Aspiration Hazard

Lung aspiration hazard if swallowed.

Medical Conditions Aggravated by Exposure

Individuals with pre-existing respiratory tract (nose, throat, and lungs), central nervous system, kidneys, and eye and/or skin disorders may have increased susceptibility to the effects of exposure.

*** Section 12 - Ecological Information ***

Ecotoxicity

According to the California Code of Regulations, a toxicity to aquatic life, specifically fish, is determined using an acute 96 hour bioassay. A material is non-hazardous if the LC_{50} is >500 mg/L. This product passed the bioassay and is considered non-hazardous.

Persistence and Degradability

This material is believed not to biodegrade.

Bioaccumulation Potential

This material is believed not to bioaccumulate.

Mobility in Soil

Expected to have high mobility in soil.

Other Adverse Effects

No additional information is available.

*** Section 13 - Disposal Considerations ***

Disposal Methods

Not regulated. Based on available data, this information applies to the product as supplied to the user. Processing, use, or contamination by the user may change the waste code applicable to the disposal of this product.

Safety Data Sheet

Material Name: SAFETY-KLEEN PREMIUM SOLVENT (VIRGIN AND RECYCLED)

SDS ID: GHS 82658

Dispose in accordance with federal, state, provincial, and local regulations. Regulations may also apply to empty containers. The responsibility for proper waste disposal lies with the owner of the waste. Contact Safety-Kleen regarding proper recycling or disposal.

*** Section 14 - Transport Information ***

Emergency Response Guide Number

128: Reference . *North American Emergency Response Guide Book*

Transportation Regulations

DOT Non-Bulk Packages (less than or equal to 119 gallons)

Not regulated.

Shipping Name: Cleaning compounds (Petroleum naphtha)(Not US DOT regulated)

Bulk Packages

Shipping Name: Combustible liquid, n.o.s. (petroleum naphtha)

UN/NA #: NA1993 **Hazard Class:** Combustible liquid **Packing Group:** III

Required Placards: Class 3, NA 1993

TDG Not regulated as dangerous goods.

*** Section 15 - Regulatory Information ***

Volatile Organic Compounds (As Regulated)

100 WT%; 6.4 to 6.7 LB/US gal; 770 to 800 g/l

As per 40 CFR Part 51.100(s).

VOC Vapor Pressure: <1.0 mmHg @ 20°C

Product may or may not be considered photochemically reactive (100% by weight).

Consult your state or local air district regulations for location specific information.

Federal Regulations

SARA 302/304

Component Analysis

Based on the ingredient(s) listed in SECTION 3, this product does not contain any "extremely hazardous substances" listed pursuant to Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) Section 302 or Section 304 as identified in 40 CFR Part 355, Appendix A and B.

SARA 311/312 Hazardous Categories

This product poses the following health hazards as defined in 40 CFR Part 370 and is subject to the requirements of sections 311 and 312 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA):

Acute Health: Yes **Chronic Health:** Yes **Fire:** Yes **Pressure:** No **Reactive:** No

SARA Section 313

Component Analysis

This product does not contain any "toxic" chemical subject to the requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR Part 372.

CERCLA

Component Analysis

Based on the ingredient(s) listed in SECTION 3, this product does not contain any "hazardous substance" listed under the Comprehensive Environmental Response, Compensation and Liability Act of 1980 (CERCLA) in 40 CFR Part 302, Table 302.4.

TSCA Inventory

All the components of this substance are listed on or are exempt from the TSCA inventory listing.

Safety Data Sheet

Material Name: SAFETY-KLEEN PREMIUM SOLVENT (VIRGIN AND RECYCLED)

SDS ID: GHS 82658

Component Analysis

Component	CAS #	TSCA
Distillates (petroleum), hydrotreated light	64742-47-8	Yes

U.S. State Regulations

This product may contain a detectable amount of benzene CAS 71-43-2, p-dichlorobenzene CAS 106-46-7, ethylbenzene CAS 100-41-4, and naphthalene CAS 91-20-3. WARNING: These chemicals are known to the State of California to cause cancer.

This product may contain a detectable amount of benzene CAS 71-43-2 and toluene CAS 108-88-3. WARNING: These chemicals are known to the State of California to cause birth defects or other reproductive harm.

Canadian Regulations

This product has been classified in accordance with the criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

Component Analysis

Component	CAS #	CAN
Distillates (petroleum), hydrotreated light	64742-47-8	DSL

Canadian WHMIS Information

B3 D2B

*** Section 16 - Other Information ***

Revision Information

Reformat to OSHA HazCom 29 CFR 1910.1200 adoption of GHS Revision 3. 7/17/15: Update to Section 9 Vapor Pressure.

Key/Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LOLI - List Of Lists™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH - Philippines; RCRA - Resource Conservation and Recovery Act; RID - European Rail Transport; RTECS - Registry of Toxic Effects of Chemical Substances®; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States

Disclaimer

User assumes all risks incident to the use of this product. To the best of our knowledge, the information contained herein is accurate. However, Safety-Kleen assumes no liability whatsoever for the accuracy or completeness of the information contained herein. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to the information or the product to which the information refers. The data contained on this sheet apply to the product as supplier to the user.

End of Sheet 82658