Product Name: **Buffing Solution** Page 1 of 4

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Buffing Solution

PART NUMBER(S): 14-100

GENERAL USE: for preparing the tire innerliner to receive a tire repair

PRODUCT DESCRIPTION: Liquid, clear

MANUFACTURER'S NAME:

31 Incorporated
STREET ADDRESS:
100 Enterprise Drive
CITY, STATE, ZIP, COUNTRY



DATE PREPARED: June 7, 2011 SUPERSEDES: Jan 1, 2010 FOR INFORMATION, CONTACT: (740) 498-8324; info@31inc.com

CITY, STATE, ZIP, COUNTRY NO. 100 A TED			EMERGENCY TELEPHONE NUMBER:					
Newcomerstown, OH 43				CHEM • TEL: (800) 255-3924 or (813) 248-0585				
		ON 2 - HAZAR	<u>DOUS INGR</u>	REDIENTS				
HAZARDOUS COMPONE	ENTS %	CAS#	TLV UNITS	Hazard	RISK PHRASES			
				Symbol	(Full Text Section 16)			
HEXANE	35 - 45	110-54-3						
HEPTANES	35 - 45	142-82-5						
ACETONE	10 - 20	67-64-1						
		ON 3 - HAZAR	DS IDENTIF	ICATION				
EMERGENCY OVERVIEW								
Contact with eyes will ca	use irritation. Contact w	ith skin may cause irrit	ation.					
ACCUTE EFFECTS OF OV								
Inhalation:	May cause dizzir	ness						
Skin:	May cause irritati	ion upon prolonged or	repeated contact					
Eyes:	May cause irritati	on, redness, tearing						
_,	,	,						
Ingestion:	May cause irritation of gastrointestinal tract.							
CHRONIC EFFECTS OF O	VEREXPOSURE:							
N/A								
OTHER HEALTH HAZARDS	S:							
N/A								
	SEC	CTION 4 - FIRS	T AID MEAS	SURES				
NHALATION:	Give oxygen							
SKIN:	Wash with soap	and large quantities of	water. If irritation	persists, seek med	dical attention.			
EYES:	Flush with large	quantities of clean wate	er for at least 15 m	inutes. Seek med	dical attention.			

Product Name: **Buffing Solution** Page 2 of 4

SECTION 5 - FIRE FIGHTING MEASURES **EXTINGUISHING MEDIA:** Foam, CO2, Dry Chemical, Fire Fighting Apparatus FIRE FIGHTING PROCEDURES: Use of self contained breathing apparatus is recommended for fire fighters UNUSUAL FIRE AND Extremely flammable and may be ignited by heat, sparks, flame, or other source of ignition. EXPLOSION HAZARDS: Closed containers can explode due to buildup of pressure when exposed to extreme heat. SECTION 6 - ACCIDENTAL RELEASE MEASURES STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: COMBUSTIBLE - Evacuate and ventilate area; remove all sources of sparks, ignition, and open flames; confine and absorb into approved absorbent; place material into approved containers for disposal following all Local, State, and Federal regulations; Do NOT wash to sewer or waterway. Note: Small amounts may be taken up with inert material. SECTION 7 - HANDLING AND STORAGE PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: This material is combustible. It should be stored in tightly closed containers in a cool, well ventilated area. Vapors may form explosive mixtures in air. All sources of ignition should be controlled. Keep this and other chemicals out of reach of children. Avoid inhaling concentrated fumes or vapors. SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION NIOSH ACGIH HAZARDOUS COMPONENTS TWA ppm TWA mg/m3 STEL ppm STEL mg/m3 TWA ppm TWA mg/m3 STEL ppm STEL mg/m3 **HEXANE HEPTANE** ACETONE PERSONAL PROTECTION: Respiratory Protection: Use NIOSH approved cartridge or gas mask. Refer to 29 CFR 1910.134 or European Standard EN 149 for complete regulations. Ventilation: Mechanical ventilation to keep product within specified TLV ranges. Protective Gloves: Imperable gloves advised. Eye Protection: Protective eyeglasses or chemical safety goggles. Refer to 29 CFR 1910.133 or European Standard EN 166. Other: Work clothes Practice safe workplace habits. Minimize body contact with this product. Work / Hygienic Practices: **SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES** VAPOR PRESSURE AT 20°C: APPEARANCE AND ODOR: Liquid, clear Solvent-like **BOILING POINT / RANGE:** SPECIFIC GRAVITY: 180 F / 82.2C FREEZING POINT: SOLUBILITY IN WATER (% by weight): N/A very slight FLASH POINT (Test Methods): V.O.C.: -15C / 9F 90%-TCC FLAMMABLE LIMITS IN AIR (% by volume): VAPOR DENSITY: 100% Heavier than air **EVAPORATION RATE:** faster than butyl acetate

Product Name: **Buffing Solution** Page 3 of 4

SECTION 10 - STABILITY AND REACTIVITY										
STABILITY:	UNSTABLE: STABLE:	XXX	CONDITIONS TO A	VOID:	Heat, Flames, sparks					
INCOMPATIBILITY (Materials to Av	void): Strong oxydize	rs								
HAZARDOUS COMBUSTION or DECOMPOSITION PRODUCTS:	CO or CO2									
HAZARDOUS POLYMERIZATION:	MAY OCCUR: WILL NOT OCCUR:	XXX	CONDITIONS TO AVOID:		N/A					
SECTION 11 - TOXICOLOGICAL INFORMATION										
HAZARDOUS COMPONENTS	CAS # EINECS #	LD50 OF INGREDIENT (Specify Species and Route)			LC50 OF INGREDIENT (Specify Species)					
EXANE 110-54-3		oral 25,000 mg rat dermal 2000 mg rabbit								
		inha	alation 171.6mg rat							
HEPTANE										
ACETONE										
SECTION 12 - ECOLOGICAL INFORMATION										

No data are available on the adverse effects of this material on the environment. Neither COD nor BOD data are available. Based on the chemical composition of this product, it is assumed that the mixture can be treated in an acclimatized biological waste treatment plant system in limited quantities. However, such treatment should be evaluated and approved for each specific biological system. None of the ingredients in this mixture are classified as a Marine Pollutant.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Dispose of in accordance with Local, State, and Federal Regulations. This product may produce hazardous vapors or fumes in a closed disposal container creating a dangerous environment. Refer to "40 CFR Protection of Environment Parts 260 - 299" for complete waste disposal regulations. Consult your local, state, or federal Environmental Protection Agency (EPA) before disposing of any chemicals. Do NOT flush to sanitary sewer or waterway.

SECTION 14 - TRANSPORT INFORMATION

PROPER SHIPPING NAME: Petroluem Distillates NOS

DOT HAZARD CLASS / Pack Group: 3 PG II

REFERENCE:

UN / NA IDENTIFICATION NUMBER: UN1268

Do not allow to enter drains, water courses or the soil.

LABEL: FLAMMABLE

HAZARD SYMBOLS:

IATA HAZARD CLASS/Pack Group: 3 PG II IMDG HAZARD CLASS: 3 PG II

RID/ADR Dangerous Goods Code: UN TDG Class / Pack Group:

Note: Transportation information if for reference only. Client is urged to consult CFR 49 parts 100 - 177, IMDG, IATA, EU, United Nations TDG, and WHMIS (Canada) TDG information manuals for detailed regulations and exceptions covering specific

container sizes, packaging materials, and methods of shipping.

Product Name: **Buffing Solution** Page 4 of 4

SECTION 15 - REGULATORY INFORMATION

TSCA (USA - Toxic Substance Control Act)

All components of this product are listed on the U.S. Toxic Substance Control Act Chemical Inventory (TSCA Inventory) or are exempted from listing because a Low Volume Exemtpion has been granted in accordance with 40 CFR 723.50.

SARA TITTLE III (USA - Superfund Amendments and Reauthorization Act)

311/312 Hazard Categories:

Immediate health

313 Reportable Ingredients:

None

CERCLA (USA - Comprehensive Response Compensation and Liability Act)

None

CPR (Canadian Controlled Products Regulations)

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

IDL (Canadian Ingredient Disclosure List)

Components of this product identified by CAS number are listed on the Canadian Ingredient Disclosure List are shown in Section 2.

DSL / NDSL (Canadian domestic Substances List / Non-Domestic Substances List)

Components of this product identified by CAS number are listed on the DSL or NDSL and may or may not be listed in Section 2 of this document. Only ingredients classified as "hazardous" are listed in Section 2 unless otherwise indicated.

EINECS (European Inventory of Existing Commercial Chemical Substances)


Components of this product identified by CAS numbers are on the European Inventory of Existing Commercial Chemical Substances.

RISK PHRASES:

R36/38 Irritating to eyes and skin

SYMBOL(S) REQUIRED FOR LABEL:





SAFETY PHRASES:

S2 Keep out of reach of childrenS41 In case of fire and/or explosion do not breathe fumes.

SECTION 16 - OTHER INFORMATION

NOTES & FULL R-PHRASE TEXT:

R36/38 Irritating to eyes and skin

HMIS HAZARD RATINGS: HEALTH 2

FLAMMABILITY 3
REACTIVITY 0

PERSONAL PROTECTIVE EQUIPMENT A

REVISION SUMMARY:

MSDS PREPARED BY: Paul Clark / President

31 Incorporated 100 Enterprise Dr.

Newcomerstown, OH 43832 740-498-8324 pclark@31inc.com

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the materials if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, vendor assumes no responsibility for injury to vendee or third person proximately caused by abnormal use of the material, even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.